

FMS Tension Control / Force Sensors

CZ-Series Compact force sensor with flexible installation options for rolls without shaft

- **Easy Installation of standard bearings**
25 mm shaft journal for standard bearings
- **For a wide range of applications**
Nominal force ratings from 50 to 1'500 N
(11 to 330 lbf.)
- **No need to change a standard machine design for special applications**
Options include high temperature and vacuum chamber (to 10⁻⁷ hPa) construction
- **Precise measuring results**
Measuring range 30:1
Accuracy class ±0.5%
- **Robust and durable**
Overload protection rating of 10-times nominal force, stainless steel sensor body




CZ-Series

The CZ-Series force sensor offers compact dimensions and flexible installation options, and are designed for the measurement of tension on continuous material processing lines where idler rolls with integrated bearings without shaft are utilized. The product can be supplied with a Pilot or without a Pilot at the back the unit. In addition, flexible mounting options include the ability to install the unit utilizing either four fasteners from the front or a single fastener from the rear. The included dowel pin can also be incorporated between force measuring bearing and the machine frame to ensure proper unit orientation. For installations where a Pillow Block mount is required the optional bracket can be utilized. The shaft journal of 25 mm diameter accepts standard bearings.

Functional description

The CZ-Series force measuring sensor combines the bearing seat and the force sensor within the same housing, thus minimizing the required installation space. The substantial overload protection translates to eliminated/minimized calibration issues due to machine upset conditions. The design includes dual bending beams, and this serves to eliminate the load specific influence of torque. The movement of the bending beams, which is proportional to the applied force, is detected by strain gauges arranged in a full bridge circuit and then converted into an electrical signal. This simple measurement principle delivers precise results even with low material tension and small web wrap angles. The Red Point, as located on the sensor body, should be aligned with the direction of the resultant force due to web tension.


CZ-Series : Dimensions



CZ-Series : Nominal forces, Weight

Size	Nominal force		Weight	
Typ	N (lbf.)		kg (.lbs)	
CZ205.50	50	(11)	1.37	(3.02)
CZ205.125	125	(27)	1.37	(3.02)
CZ205.250	250	(55)	1.37	(3.02)
CZ205.500	500	(110)	1.37	(3.02)
CZ205.1000	1000	(220)	1.37	(3.02)
CZ205.1500	1500	(337)	1.37	(3.02)

CZ-Series : Installation option



CZ-Series : Technical data	
Sensitivity	1.8 mV / V
Tolerance of sensitivity	< ±2%
Accuracy class	±0.5% (F _{Nom})
Temperature coefficient	±0.1% / 10 K
Temperature range	-10 °C to +60 °C (14 F to 140 F)
Input resistance	350 Ω
Power supply	1 to 10 VDC
Overload protection	10-times nominal force F _{Nom}
Material main body	Stainless steel
Protection class	IP 42
Electrical connection	Male receptacle, flange mounting M14x1, 5-pole
Repeatability error	0.05%
Measuring range	30:1


CZ-Series : Order code	
CZ 205 .1000 .25 .PH .H14	
	Options
	Installation option PH with pilot hole for centering
	Journal diameter in mm
	Nominal force rating in N
	Size
	Series

CZ-Series : Options	
FL	flat face of force sensor, without shoulder, single screw mount, with dowel pin
PH	flange mount with 4 screws, pilot hole for centering
H14	right-angle connector in scope of supply, replaces straight connector
H16	temperature range up to 120°C (248°F)
H21	electrical connection with PG gland with 5 m (16 ft.) cable, replaces connector
H31	for vacuum applications to 1E-7 hPa 1E-5 Torr, temperature range up to 120°C (248°F)
H32	vacuum to 1E-7 hPa 1E-5 Torr, up to 150°C (302°F), with pg-gland and 5 m (16 ft.) cable
H33	temperature range up to 150°C (302°F), with pg-gland and 5 m (16 ft.) cable

CZ-Series : Scope of supply	
<ul style="list-style-type: none"> ● force sensor ● straight connector (female) ● clip ring ● installation option PH: 4 pcs. DIN912 M6 x 40 ● installation option FL: dowel pin 	

CZ-Series : Accessories	
<ul style="list-style-type: none"> ● cable, 1 m (3.25 ft.) without connector ● cable, 10 m (32.8 ft.) without connector ● cable, 5 m (16.4 ft.) without connector ● cable, 2 m (6.5 ft.) without connector ● connector M14 x 1, 5-pole, straight ● connector M14 x 1, 4-pole, right angle ● installation bracket CA203.MB 	

CZ-Series : Typical application with installation bracket



Other products : Tension Control

Measuring Amplifiers



Tension Controllers



Intrinsically Safe Barrier



About us

FMS Force Measuring Systems AG is the market leader in the field of web tension measurement, control and specialist for web guiding solutions. For the wire industry we are the only manufacturer offering a complete range of technologies for force measurement, data processing and radio transmission of signals.

Our in house developed products are used in the manufacturing industry, converting, metals, paper, textiles, as well as in cable and wire rope production. Utilising the latest technology, high quality components and a firm understanding of customer applications, FMS supports customers worldwide in the effort to maximize the productivity of their machines. Since 1993, our highly qualified employees have been creating high-end solutions for machine builders and plant operators. As an owner-managed company, we pride ourselves on being personal and approachable with the ability to make decisive moves fast.

World Headquarters: FMS Force Measuring Systems AG

Aspstrasse 6 • 8154 Oberglatt (Switzerland) • Phone + 41 44 852 80 80 • Fax + 41 44 850 60 06
info@fms-technology.com • www.fms-technology.com